





## Temperature Sensor

UIO-G4RL-TES





# Temperature Sensor

UIO-G4RL-TES

## Ruggedised IoT Flood Sensor

The Urban.io Temperature Sensor allows you to accurately monitor the temperature of the air within a room, enclosure or open space.

Used in conjunction with an Urban.io Gateway the Temperature Sensor will read and transmit the current ambient temperature to the Urban.io Cloud Platform on a near real-time basis.

Measured data is securely displayed within the Urban.io Cloud Platform for reporting purposes. Through the use of dynamic profiles, thresholds can be set for each sensor which can trigger alarms that can be sent via email or SMS.


All recorded sensor data, historical summaries and alarms are made available for use within external software platforms via the IoT Data API.



## Sensor Operation

Temperature Sensor measures temperature in degrees celsius every 10 minutes and sends the results to the server.


Cloud Reporting Platform



IoT API

```
ices": [
{
  "id": 11,
  "position": "Office",
  "display_type": "temperature",
  "operator_id": 41,
  "order_by_status": false,
  "hardware_device_id": "device
  "logical_datastreams": [
    {
      "id": 44,
      "display_type": "SENSOR_BA
      "sensor_network": true,
      "measure": {
        "id": 1,
        "name": "Sensor Battery"
        "requires_multiplier": n
        "series_type": "continuo
```

Email/SMS Alerts



○ Can be retrofit into any location in less than 10 minutes, with no special equipment required.



# Features

Temperature Sensor / UIO-G4RL-TES

## Core Features

### Primary Sensing Element:

- Digital temperature sensor integrated circuit

### Secondary Sensing Elements:

- Fault detection (loss of sensing element)
- IoT network connectivity (Signal to Noise levels "SNR")
- IoT device battery Level (% of remaining battery level)

### General Sensor Features:

- Gateway to sensor network range:
  - 500m non-line-of-sight
  - 5km line-of-sight
- Operating Temperature: -40° to 85°C
- Power Supply: 3.0 V CR2477 coin cell battery (replaceable)
- Battery life: 2 years under normal operation
- Reading frequency: 1 Sample each 1 minute interval
- Data transmission frequency: 10 minute interval

## Variants

Each sensor is packaged with three pluggable/snap-in antennas for use depending on the region you are deploying them into.

### 915 Band (915–925 MHz)

Suitable for South East Asia,  
Australia, North/South America

### 868 Band (863–870 MHz)

Suitable for Africa, Middle East, Europe

### 780 Band (779–787 MHz)

Suitable for China

## Example Applications

Freezer / cooler door monitoring



Environmental monitoring



HVAC testing



Data center monitoring



○ Can be retrofit into any location in less than 10 minutes, with no special equipment required.



# Specifications

Temperature Sensor / UIO-G4RL-TES

## Technical Specification

Maximum resolution over measured electrical range	<b>16,383 detectable points</b>
Measurement range	<b>-40 to 125°C</b>
Calibration / Drift	<b>None</b>
Accuracy	<b>± 0.1°C</b>
Temperature range (limited by battery)	<b>-20°C to 85°C</b>

## Data Sampling and Reporting Frequency Specification

Standard measurement reporting heartbeat	<b>10 minutes</b>
Standard measurement interval	<b>10 seconds</b>
High resolution measurement interval (magnet mode)	<b>10 seconds</b>
Priority event reporting	<b>No</b>
Priority events reported per heartbeat	<b>NA</b>

## Power Specification

Supply Voltage	<b>2.0 – 3.4 DVC</b> replaceable CR2477 1AH lithium metal battery
Current consumption – sleep mode	<b>6 uA</b>
Current consumption – sensor active sampling mode	<b>120 uA mS</b>
Current consumption – radio RX mode	<b>25 mA for 0.5 seconds</b>
Current consumption – radio TX mode (max)	<b>100 mA for 0.5 seconds</b>

 Can be retrofit into any location in less than 10 minutes, with no special equipment required.



# Specifications

Temperature Sensor / UI0-G4RL-TES

## Environment Specification

Enclosure rating	IP67
Operating temperature electronic circuit board	-40°C to +85°C
Operating temperature CR2477 coin cell battery	-40°C to +85°C

## Network Specification

Radio modulation	LoRa
Radio protocol	Urban.io IoT Generation 4.x
Frequency bands	780 MHz, 868 MHz, 915 MHz, 4th configurable
Frequency accuracy	±30kHz (±30ppm max)

### 915 MHz Band

Maximum output power	+17 dBm
Default channel low, channel high	923.3 MHz, 925.1 MHz
Default bandwidth	500 kHz

### 868 MHz Band

Maximum output power	+17 dBm @ 869.5, +12 dBm others
Default channel low, channel high	868.1 MHz, 869.5 MHz
Default bandwidth	125 kHz

### 780 MHz Band

Maximum output power	+17 dBm
Default channel low, channel high	779.9 MHz, 783.0 MHz
Default bandwidth	250 kHz

## Security Specification

Sensor data encryption	AES 128-Bit
------------------------	-------------

## Certifications

CE	EN 301 489-x (EMC), EN60950 (safety)
FCC	CFR47, Part 15 for 915 MHz


○ Can be retrofit into any location in less than 10 minutes, with no special equipment required.




# Dimensions and Mounting

Temperature Sensor / UIO-G4RL-TES

## Top View



## Side View



## Dimensions

**Length:**  
73 mm (with antenna)

**Height:**  
29 mm


**Width:**  
44 mm

**Weight:**  
85 g

## Mounting

### Option: A

Magnetic Attachment




Magnetic feet snap to any metal surface

### Option: B

Industrial Sensor Clip

SKU: UIO-G4RL-INC




Option to 3M VHB stick Industrial Clip onto surface  
Option to Tek Screw Clip into surface

Magnetic feet snap and twist click into Industrial Clip mount

### Option: C

Architectural Sensor Base

SKU: UIO-G4RL-BAS



Option to 3M VHB feet pads to stick Industrial Clip onto curved surface

Snug fit into recess magnetic feet snap onto metal base of Architectural Mount

3M VHB stick Architectural Mount onto any flat surface

○ Can be retrofit into any location in less than 10 minutes, with no special equipment required.



## Positioning & Usage

Temperature Sensor / UI0-G4RL-TES

### Correct Positioning

This product is designed for usage with an Urban.io IoT Gateway. In ideal conditions with correct orientation of sensors and gateway antennas the following ranges can be achieved.

**Up to 5km line-of-sight** where there are no obstructions between the gateway and the sensor and they are placed on the same horizontal plane.

**500m non-line-of-sight** in an enclosed space where there are one or more obstructions (objects, walls, buildings) between the gateway and the sensor and it is placed on the same horizontal plane.

Where the sensors and gateways are placed in an enclosed space, the range can vary significantly. In addition incorrect antenna orientation, placement on different vertical planes, interruptions by walls, doors, boxes, ducts, pipes, machinery or any other large dense physical objects can affect the range even further. It is advised to avoid installation inside metal containers or behind metal objects.

### Correct Usage

This product is designed for application in normal indoor and certain outdoor environments. The gateway housing is IP65 rated and as such is designed to be water and dust resistant as well as generally resistant to direct sunlight. However the 240v Power Adapter is not rated for outdoor usage.

Please avoid the following:

- Environments where there is extreme heat (above +60°C) or cold (below -20°C)
- Environments where there is corrosive gas or fluids
- Environments which cause intermittent connectivity between gateway and sensors; this increases the frequency that sensors will scan for available networks and cause batteries to drain prematurely

### Certifications





# Connecting IoT Data to External Software Platforms

Temperature Sensor / UIO-G4RL-TES

Urban.io proactively supports the interfacing of IoT sensor data with all industry leading Asset Management, Field Force and Work Management, Data Analytics and Machine Learning Platforms.

We provide the following Public APIs as well as pre-built API Adapters for the following Enterprise IoT Systems:

## Public APIs



Rest Web Services



MQTT

## API Adapters



AWS IoT Core



IBM Watson IoT



Azure IoT Hub

If you wish to interface our IoT device data with a platform not on this list please contact [enquiries@urban.io](mailto:enquiries@urban.io)